


SPECIFICATION	CONNECTION	VALUE
NUMBER OF PHASE		5.00
AMPS/PHASE		3.00
RESISTANCE/PHASE(Ohms)@25°C		0.86±10%
INDUCTANCE/PHASE(mH)@1KHz		16±20%
HOLDING TORQUE(Nm)[lb-in]		3.20[28.32]
STEP ANGLE(°)		0.36/0.72
STEP ACCURACY(NON-ACCUM)		±5.00%
ROTOR INERTIA(g-cm ²)		—
WEIGHT(Kg)[lb]		—
TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED)		
AMBIENT TEMPERATURE -20°C~50°C[-4°F~122°F]		
INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY)		
INSULATION CLASS B 130°C[266°F]		
DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE)		
AMBIENT HUMIDITY MAX.85%(NO CONDENSATION)		



	APVD		5.5.2023
	CHKD		
1:1.5	DRN		
SCALE	SIGNATURE	DATE	

STEPPER MOTOR

35VR26-3005S