


SPECIFICATION	VALUE
NUMBER OF PHASE	3.00
AMPS/PHASE	5.00
RESISTANCE/PHASE(Ohms)@20°C	2.20±10%
INDUCTANCE/PHASE(mH)@1KHz	26.00±20%
HOLDING TORQUE(Nm)[lb-in]	36.00[318.87]
STEP ANGLE(°)	1.20
STEP ACCURACY(NON-ACCUM)	±5.00%
ROTOR INERTIA(g-cm ²)	34000.00
TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED)	
AMBIENT TEMPERATURE -20°C~50°C[-4°F~122°F]	
INSULATION CLASS B 130°C[266°F]	
DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE)	

TYPE OF CONNECTION (EXTERN)		MOTOR
PIN NO	BIPOLAR	LEADS
1	U	RED
2	V	YEL
3	W	GRN
4	GND	BLK



STEP	1	2	3	4	5	6
U	+	-	-	-	-	+
V	-	-	-	+	+	-
W	-	+	+	-	-	-

→ CW

SCALE	APVD		4.18.2019
	CHKD		
	1:2.5	DRN	
	SIGNATURE		DATE

STEPPER MOTOR

52HT87-5003S